



Green iron and steel – safe DRI shipping

By [Stephen B. Harrison](#) on Aug 15, 2023

[FEATURE](#) | [POWER](#)

The modern maritime industry relies on gas and flame detection for safe operations. LNG tankers, LPG tankers, crude oil tankers and refined products tankers carry thousands of tonnes of flammable, volatile hydrocarbons. The requirement for flammable gas detection and flame detection with these cargoes is clear.

As shown in Table 1, bulkers transport thousands of tonnes of coal and iron ore daily. Fertilisers and food grains are also common bulk cargoes. Many bulk cargoes, such as cement, present a low degree of hazard with minimal gas detection requirements. Others such as coal, DRI and ammonium nitrate granules present hazards that must be monitored using gas detection equipment.

DRY BULK CARGO	ANNUAL TONNAGE (MILLIONS), 2022	SIGNIFICANT EXPORTERS
IRON ORE	1,570	Australia, Brazil, Canada, South Africa
STEAM COAL	934	Indonesia, Australia, South Africa
OTHER ORES AND MINERALS	850	UAE, Australia, Vietnam, USA
COKING COAL	291	Australia, USA, Canada
WHEAT AND GRAINS	290	USA, Argentina, Brazil, Australia
FERTILISERS	177	China, Morocco, Canada
BAUXITE	169	Guinea, Australia, Indonesia, Brazil
SOYBEANS	136	Brazil, USA, Argentina, Uruguay
NICKEL ORE	55	Philippines, Indonesia, New Caledonia, Ivory Coas

Table 1 - Annual tonnages of some commonly traded bulk cargoes

International Maritime Codes

The International Maritime Solid Bulk Cargoes (IMSBC) Code lists 450 solid bulk cargoes and describes their characteristics and required precautions. The hazardous properties of the cargoes are categorised in three main groups.

1. Group A – cargoes which may liquefy if shipped at a moisture content exceeding their Transportable Moisture Limit (TML).
2. Group B – cargoes which possess a chemical hazard which could give rise to a dangerous situation on a ship.
3. Group C – cargoes which are neither liable to liquefy (Group A) nor possess chemical hazards (Group B).

Group B cargoes are those that are most likely to require gas and flame detection equipment. Amongst others, they include the following bulk cargoes.

1. Direct reduced iron (DRI) may react with water and air to produce hydrogen and heat. The heat produced may cause ignition. Oxygen in enclosed spaces may also be depleted.
2. Coal may create flammable atmospheres, heat spontaneously and deplete oxygen. Some types of coal can produce carbon monoxide or methane.
3. Ammonium nitrate-based fertilisers support combustion. If heated, contaminated or closely confined, they can explode or decompose to release toxic fumes and gases.

Iron making with oxygen and hydrogen

The classical way to convert iron ore to iron is in a blast furnace where coke is used to reduce the iron ore to iron and carbon dioxide (CO₂) gas is emitted. Thousands of tonnes of oxygen are produced each day on air separation units and fed to blast furnaces to assist the process. In the future, iron making must decarbonise. Changes to the blast furnace are likely and the use of alternative reducing agents such as hydrogen and the direct reduction of iron can minimise CO₂ emissions.



Direct Reduced Iron (DRI) is produced by passing hot reducing gases such as hydrogen, natural gas, or syngas over iron ore. DRI can be produced as briquettes which are sometimes referred to as hot briquetted iron (HBI), pellets, or lumps. HBI and DRI are likely to become major international cargoes as 'green steel' made from green hydrogen becomes more popular.

Read more: [Will DRI be key to producing sustainable steel?](#)

DRI and HBI have porous structures, which makes them prone to re-oxidation on contact with air or moisture. This causes self-heating, leading to cargo temperatures of more than 900 °C. Contact with moisture liberates hydrogen, an extremely flammable gas. This phenomenon has caused serious incidents.

Gas detection for DRI cargoes

In 2003 the bulk carrier ADAMANDAS was lost following overheating of her cargo of 21,000 tonnes of DRI pellets. The holds were inerted with nitrogen in Trinidad prior to departure to Indonesia.

Whilst the ADAMANDAS was berthed in Durban, problems with the DRI cargo were observed. High temperatures (>250 °C), high oxygen concentrations (19.9%) and high hydrogen gas concentrations (33ppm) were measured in cargo hold number two. On several occasions, a total of 63.5 tonnes of vapourised liquid nitrogen was injected into that hold. Eventually, the cargo temperature, oxygen level and hydrogen level fell below acceptable values and the ship set sail.

During passage to Surabaya the temperature in hold two increased to 380 °C, resulting in a decision to spray the DRI cargo with water. However, the temperature continued to rise to 820 °C and the hydrogen gas concentration in hold two was measured to be 100%. The vessel was sunk using a controlled explosion off the island of Réunion since the situation was determined to be out of control.

In a later incident during 2004, hydrogen explosions in four of her five cargo holds caused the loss of the bulk cargo vessel YTHAN off Colombia. Hydrogen had been produced from a cargo of damp DRI fines.

Requirements and regulations

Following these incidents, in 2011 changes to the IMSBC Code related to DRI and HBI came into effect. The IMSBC Code categorises three types of DRI. DRI (A) is a high-density, low-reactivity variety known as Hot Briquetted Iron (HBI), or Hot Moulded Briquettes (HMB). DRI (B) is highly reactive, low density DRI in the form of lumps and pellets and cold moulded briquettes. DRI (B) may only be carried under an inert gas atmosphere. DRI (C) relates to by-products and fines and has the same requirements as DRI (B).

Some points from the Code of most relevance to gas detection are summarised here.

a) All Types of DRI

1. The ship shall be provided with a detector suitable for measuring hydrogen in an oxygen depleted atmosphere and for use in a flammable atmosphere.
2. Cargo temperatures and hydrogen concentrations in hold atmospheres are to be monitored during the voyage.
3. The hydrogen concentration is to be measured in holds prior to opening hatch covers.

b) DRI (A), Briquettes, hot-moulded

1. The maximum limit on the moisture content is 1%.
2. The cargo is to comprise essentially whole briquettes.
3. Surface ventilation only shall be conducted as necessary.

c) DRI (B), Lumps, pellets, cold-moulded briquettes

1. Carriage is only permitted under an inert gas blanket.
2. The ship shall be provided with the means of reliably measuring the temperature at several points within the stow and determining the concentrations of hydrogen and oxygen in the cargo space atmosphere on voyage whilst minimising loss of the inert atmosphere.
3. The ship shall be provided with the means to ensure that the requirement to maintain the oxygen concentration below 5% can be achieved throughout the voyage. The ship's fixed CO₂ fire-fighting system shall not be used for this purpose.
4. The ship shall not sail until the master and a competent person are satisfied that: all loaded cargo spaces are correctly sealed and inerted; the cargo temperatures have stabilised at all measuring points and are less than 65 °C; the concentration of hydrogen in the free space has stabilised and is less than 0.2% by volume, which equates to 5% of the lower explosive limit (LEL).
5. The ship shall be provided with a detector suitable for measuring oxygen in a flammable atmosphere.
6. The oxygen concentration in the hold atmosphere shall be maintained at less than 5% throughout the voyage.

The Code also categorises DRI (C), By-products and fines. In this case, the average particle size is less than 6.35mm, and there are to be no particles greater than 12mm in size. The reactivity of this cargo is extremely difficult to assess due to the nature of the material that can be included in the category. A worst-case scenario should therefore be always assumed meaning that the carriage requirements are identical to those for DRI (B).

Regulation 3 also confirms the requirement to measure oxygen deficiency.

1. When transporting a solid bulk cargo which is liable to emit a toxic or flammable gas, or cause oxygen depletion in the cargo space, an appropriate instrument for measuring the concentration of gas or oxygen in the air shall be provided together with detailed instructions for its use.
-